



75W-90 GL 3/4/5

Synthetic transmission oil for manual gearboxes and final drives

Description:

COMLINE Transyn 75W-90 is a synthetic, universal transmission/gear oil which can be applied in both manual gearboxes as well as in final drives, where an API GL-3, 4 or 5 quality oil is prescribed. By this, the product can reduce the stock of transmission/gear oils.

COMLINE Transyn 75W-90 can be used for the complete drive line. The product contains special additives reducing fuel consumption and eliminating shifting problems. Due to this unique formulation not only wear, but also corrosion and foam building are reduced to a minimum. At high temperatures the oil is protected against thermal oxidation.

COMLINE Transyn 75W-90 can be used in synchromesh gearboxes and ensures easy and smooth shifting, even at low temperatures.

COMLINE Transyn 75W-90 shows excellent EP (Extreme Pressure) characteristics to cope with heavy loads and vibrations. Viscosity drop, caused by heavy loads, is minimal so that this oil guarantees the right viscosity, even at prolonged drain intervals

Performance level:

API MT-1 ; API GL 3/4/5 ; MIL-L-2105
B/C/D ; ZF TE-ML
02B/05A/07A/08A/12E/16B/
16C/16D/17B/19B/21A ; Mack GO-J ; MIL-
PRF-2105E ; Volvo 97310 ; Scania STO
1:0 ; DAF ; MAN M 3343 Typ M ; MAN 342
Type M2 ; MAN 341 Type Z2

Typical properties:

75W-90

| | | |
|-----------------|------|-------|
| Density 20°C | Kg/L | 0.883 |
| Viscosity 100°C | cSt | 15.0 |
| Viscosity 40°C | cSt | 86.7 |
| Viscosity Index | | 183 |
| Flash point | °C | 144 |
| Pour point | °C | -42 |