

COMLINE 80W90 GL-5



SAE 80W-90 GL-5

Mineral gear oil for hypoid gears and hub reductions

Description:

COMLINE HPG Gear Oil is a mineral gear oil, formulated according to the latest phosphor - sulphur technology. This special additive technology assures an excellent protection against metal-to-metal contact of the gears under the most severe operating conditions, even under shock loads.

COMLINE HPG Gear Oil contains special additives, leaving a protecting oil film for optimum corrosion protection. Furthermore, the SAE 80W and 85W-140 viscosity grades have an excellent low temperature fluidity for an optimum performance during all seasons.

COMLINE HPG Gear Oil shows an excellent oxidation and thermal stability. Seals are not affected by this product.

COMLINE HPG Gear Oil is recommended for use in hypoid gears, hub reductions, gearboxes, PTO's and differentials where an API GL-5 , MIL-L 2105-D and Mack GO-G are recommended. The SAE 85W-90 viscosity grade can also be applied where MB 235.0 is prescribed.

Performance level:

SAE 80W-90
API GL-5 ; MIL-L-2105 B/C/D

Typical properties:

80W-90

Density 20°C	Kg/L	0.886
Viscosity 100°C	cSt	14.1
Viscosity 40°C	cSt	137
Viscosity -12°C	cP	-
Viscosity -26°C	cP	140000
Viscosity Index		100
Flash point COC	°C	>210
Pour point	°C	-33



THE RECOMMENDATIONS OR SUGGESTIONS MADE IN THIS SHEET ARE MADE WITHOUT GUARANTEE OR REPRESENTATION AS TO RESULTS. THE CONTENT OF THIS SHEET IS CORRECT TO THE BEST OF OUR KNOWLEDGE. WE ADVISE THE READER TO CAREFULLY EVALUATE THE PRODUCT CHOICE FOR CRITICAL APPLICATIONS TOGETHER WITH THE SUPPLIER. WE DO NOT ACCEPT RESPONSIBILITY FOR DAMAGE AS A CONSEQUENCE OF INCOMPLETENESS OR, NEGLIGENCE AND INACCURACIES IN THIS INFORMATION SHEET. ALL TERMS OF SALE OF THE SUPPLIER CAN BE APPLIED HERE.