



Comline CO 20W50 CG4

20W-50

Mineral motor oil for mixed fleet

Description:

Comline CO 20W50 CG4 has been developed according to the latest oil consumption and exhaust emission requirements and protects against oil thickening and wear. It has an excellent deterging capability.

Comline CO 20W50 CG4 amply fulfils the latest, strict norms regarding deposits on piston crowns, in top piston ring grooves and on the rest of the pistons.

Comline CO 20W50 CG4 is especially suitable for mixed fleet applications like petrol, LPG and light loaded diesel engines, whether or not turbo charged and/or with catalytic converter. Because of its broad application, this oil can reduce the stock level for the fleet owner and the retailer.

Performance level:

API: SJ/CG-4/CF-4/CF
ACEA: A2/B3/E2 en A3 (98)
VW 501.00/505.00
MB: 228.1, 229.1
Volvo: VDS
MAN: 271
Mack: EO/-L

Typical values:

20W-50

Density 20°C	Kg/L	0.885
Viscosity 100°C	cSt	17.8
Viscosity 40°C	cSt	159.1
Viscosity -15°C	cP	<9500
Viscosity -20°C	cP	-
Viscosity -25°C	cP	-
Viscosity Index		123
Flash point COC	°C	214
Pour point	°C	-24
Sulphated ash	Wt%	1.10

THIS SHEET CONTAINS RECOMMENDATIONS OR SUGGESTIONS ON PROPERTIES AND POSSIBLE APPLICATIONS OF COMLINE PRODUCTS. BECAUSE OF CONTINUOUS PRODUCT RESEARCH AND DEVELOPMENT, THE INFORMATION IN THIS DOCUMENT CAN BE CHANGED AT ALL TIMES, WITHOUT FOREGOING NOTICE. THE ANALYTICAL INFORMATION IN THIS DOCUMENT CONSISTS OF TYPICAL VALUES. ALTHOUGH THE TEXT HAS BEEN REDACTED WITH GREAT CAREFULNESS, THE AUTHOR WILL NOT ACCEPT ANY LIABILITY FOR DAMAGES CAUSED BY INCOMPLETENESS AND/OR INCORRECTNESS OF THE TEXT. THE READER IS ADVISED TO MAKE THE FINAL PRODUCT CHOICE IN DIALOGUE WITH THE SUPPLIER.